

Diamètre	model goujon	couple serr maxi de l'écrou Nm	Nature tôle	effort de pose KN	force extraction N	couple foirage Nm	force de traction N
M3 perçage 4,2	acier FH	0,55	Aluminium	4,9	710	1,24	1245
	inox FHS	0,44	1,5mm	9,8			996
	acier FH	0,55	Acier	4,9	1000	2,15	1465
	inox FHS	0,44	1,5mm	9,8			1172
3,5 M3 perçage 5,4	acier FH	0,55	Aluminium	7,6	1330	2,82	1245
	inox FHS	0,444	1,5mm	14,7			996
	acier FH	0,55	Acier	7,6	1860	3,95	1465
	inox FHS	0,44	1,5mm	14,7			1172
M4	acier FH	2	Aluminium	10,7	1780	5,08	2575
	inox FHS	1,6	1,5mm	17,8			2060
	acier FH	2	Acier	10,7	2490	8,47	3110
	inox FHS	1,6	1,5mm	17,8			2488
M5	acier FH	3,6	Aluminium	10,7	1780	5,08	2575
	inox FHS	2,88	1,5mm	17,8			2060
	acier FH	3,6	Acier	10,7	2490	8,47	3110
	inox FHS	2,88	1,5mm	17,8			2488

